



GLOCK 17



FRONT SIGHT
polymer



SLIDE STOP LEVER
standard

TRIGGER CONFIGURATION
triggerspring / connector 1 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
17 rds



MAGAZINE CATCH
standard



PERFECTION

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

17 rds



BARREL PROFILE

hexagonal



BARREL LENGTH

mm in.
114 4,49



LENGTH OF TWIST

mm in.
250 9,84



WEIGHT

without magazine
g oz
625 22,05



WEIGHT

with empty magazine
g oz
705 24,87



WEIGHT*

with loaded magazine
g oz
915 32,28



TRIGGER TRAVEL

mm in.
12,5 0,49

TRIGGER PULL

N lbf
28 6,3

* depending on the ammunition used

DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	204	8,03
2. SLIDE LENGTH (cpl.)	186	7,32
3. WIDTH (OVERALL)	32	1,26
4. SLIDE WIDTH	25,5	1,00
5. HEIGHT INCL. MAGAZINE	139	5,47
6. SIGHT RADIUS (POLYMER)	165	6,50
SIGHT RADIUS (STEEL)	164	6,46
SIGHT RADIUS (GNS)	163	6,42
7. TRIGGER DISTANCE	72	2,83
8. BARREL DISTANCE	20	0,79