



GLOCK 19



FRONT SIGHT
polymer



SLIDE STOP LEVER
standard

TRIGGER CONFIGURATION
triggerspring / connector 1 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
15 rds



MAGAZINE CATCH
standard



PERFECTION

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

15 rds



BARREL PROFILE

hexagonal



BARREL LENGTH

mm in.

102 4,02



LENGTH OF TWIST

mm in.

250 9,84



WEIGHT

without magazine

g oz

600 21,16



WEIGHT

with empty magazine

g oz

670 23,63



WEIGHT*

with loaded magazine

g oz

855 30,16



TRIGGER TRAVEL

mm in.

12,5 0,49

TRIGGER PULL

N lbf

28 6,3

* depending on the ammunition used

DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	187	7,36
2. SLIDE LENGTH (cpl.)	174	6,85
3. WIDTH (OVERALL)	32	1,26
4. SLIDE WIDTH	25,5	1,00
5. HEIGHT INCL. MAGAZINE	128	5,04
6. SIGHT RADIUS (POLYMER)	153	6,02
SIGHT RADIUS (STEEL)	152	5,98
SIGHT RADIUS (GNS)	151	5,94
7. TRIGGER DISTANCE	71,2	2,80
8. BARREL DISTANCE	20	0,79