



GLOCK 19 Gen5/FS



FRONT SIGHT
polymer



SLIDE STOP LEVER
ambidextrous

TRIGGER CONFIGURATION
triggerspring01 / connector 5 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
15 rds



MAGAZINE CATCH
reversible



PERFECTION

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

15 rds



BARREL PROFILE

hexagonal (GMB)



BARREL LENGTH

mm in.

102 4,02



LENGTH OF TWIST

mm in.

250 9,84



WEIGHT

without magazine

g oz

610 21,52



WEIGHT

with empty magazine

g oz

670 23,63



WEIGHT*

with loaded magazine

g oz

855 30,16



TRIGGER TRAVEL

mm in.

12,5 0,49

TRIGGER PULL

N lbf

26 5,8

* depending on the ammunition used

DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	185	7,28
2. SLIDE LENGTH (cpl.)	174	6,85
3. WIDTH (OVERALL)	34	1,34
4. SLIDE WIDTH	25,5	1,00
5. HEIGHT INCL. MAGAZINE	128	5,04
6. SIGHT RADIUS (POLYMER)	153	6,02
SIGHT RADIUS (STEEL)	152	5,98
SIGHT RADIUS (GNS)	151	5,94
7. TRIGGER DISTANCE	70	2,76
8. BARREL DISTANCE	20	0,79

VARIABLE DIMENSIONS

		mm	in.
MEDIUM BACKSTRAP (+ 2 mm 0.08 in.)	1. LENGTH (OVERALL)	187	7,36
	7. TRIGGER DISTANCE	72	2,83
LARGE BACKSTRAP (+ 4 mm 0.16 in.)	1. LENGTH (OVERALL)	189	7,44
	7. TRIGGER DISTANCE	74	2,91