



GLOCK 43



FRONT SIGHT
polymer



SLIDE STOP LEVER
standard

TRIGGER CONFIGURATION
triggerspring01 / connector 7 /
firing pin spring 24N (silver)



PERFECTION



REAR SIGHT
polymer



MAGAZINE
6 rds



MAGAZINE CATCH
reversible

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

6 rds



BARREL PROFILE

hexagonal (GMB)



BARREL LENGTH

mm in.

87 3,41



LENGTH OF TWIST

mm in.

250 9,84



WEIGHT

without magazine

g oz

460 16,23



WEIGHT

with empty magazine

g oz

510 17,99



WEIGHT*

with loaded magazine

g oz

585 20,64



TRIGGER TRAVEL

mm in.

12,5 0,49

TRIGGER PULL

N lbf

24 5,4

* depending on the ammunition used

DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	159	6,26
2. SLIDE LENGTH (cpl.)	154	6,06
3. WIDTH (OVERALL)	27	1,06
4. SLIDE WIDTH	22	0,87
5. HEIGHT INCL. MAGAZINE	108	4,25
6. SIGHT RADIUS (POLYMER)	133	5,24
SIGHT RADIUS (STEEL)	132	5,20
SIGHT RADIUS (GNS)	131	5,16
7. TRIGGER DISTANCE	65	2,56
8. BARREL DISTANCE	19	0,75